



H-1221N Solvent-Based Non-Silicone Defoamer

Product Description:

This is a solvent-based non-silicone defoaming agent, composed of defoaming substances without organic silicone. It provides fast defoaming effects, effectively suppressing and eliminating bubbles that may form during the production and application of coatings. It is suitable for epoxy, unsaturated polyester, and PVC coatings.

Typical Physical Properties:

Parameter	Value
Appearance	Light yellow liquid
Density (25°C, g/cm ³)	0.9
Active Ingredient Content (%)	20
Flash Point (°C)	30
Refractive Index (25°C)	1.49
Solvent	Xylene

Application Range:

- Wood coatings
- Industrial coatings

Recommended Dosage:

0.1 - 1.0% of the total formulation.

Usage Method:

It can be added during the production process when defoaming is needed.

Packaging:

Available in 25KG/180KG non-recyclable plastic or iron drums. Ensure that the container is tightly sealed after each use if not fully emptied.

Storage:

Store away from heat sources, open flames, and direct sunlight.



SIO New Material

Sincerity, Collaboration, Innovation, Development

Shelf Life:

The product has a shelf life of 18 months from the date of production.

The above information is provided based on current knowledge of the product and serves as an introduction and usage suggestion for our product. It should not be interpreted as a guarantee of specific characteristics for particular applications. Therefore, we assume no responsibility for this introduction and suggestions, and they do not replace the necessary evaluations and tests users should conduct before using the product.